## Recess/surface mounted lights

Modular multi-white, drill hole Ø: 58 mm (2 5/16")





Häfele Loox5 LED 2091/3091





> Dimmable: Yes Aluminum > Material:

> Energy efficiency class:

IP44 as recess mounted light > Degree of protection: IP20 as surface mounted light

> Mounting: For mounting in drilled hole, for clamp

or screw fixing 58 mm (2 5/16")

> Drill hole Ø: > Supplied with: 1 light module

| 2700 K  | 5000 K                | 80°      |         |             |
|---------|-----------------------|----------|---------|-------------|
| 2000 lx | 2100 lx               | ***      | 250 mm  | (9 13/16")  |
| 520 lx  | 550 lx                | **       | 500 mm  | (19 11/16") |
| 220 lx  | 23 <mark>5 l</mark> x |          | 750 mm  | (29 1/2")   |
| 120 lx  | 125 lx                | <b>*</b> | 1000 mm | (39 3/8")   |



The IP44 degree of protection is reduced to IP20 when surface mounting or recess mounting with through hole.

Loox lights and drivers are "Suitable for use within closet storage spaces"

## Order reference

Please order lead and housing separately, see page 45.



5 12 V

Loox5 12 V driver see page 124



Loox5 24 V driver see page 125



Color control only via 6-way distributor Häfele Connect Mesh with multi-white adapter and remote control or smartphone. Please order separately, see Networking page 95.

Jimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice



## Recess/surface mounted lights


Modular multi-white, drill hole Ø: 58 mm (2 5/16")


## Häfele Loox5 LED 2091/3091

| < Voltage | s Quantity | X Color<br>temperature | ■ Wattage | I Luminous<br>flux | Fuminous efficacy | <sub>e</sub> a Color<br>rendering<br>index<br>CRI | $R_{s}$ | Weighted energy consumpt. | Item No.   |
|-----------|------------|------------------------|-----------|--------------------|-------------------|---|---------|---------------------------|------------|
| 5 12 V    | LED 2091   |                        |           |                    |                   |   |         |                           |            |
|           | 12         | 2700<br>5000           | 3.4       | 240<br>270         | 72<br>80          | >90   | >55     | 3.74                      | 833.72.478 |
| Faur      | 1.70.000   |                        |           |                    |                   |   |         |                           |            |
| 5 24 V    | LLD 0031   | 2700                   |           | 240                | 72                |   |         |                           |            |
|           | 12         | 5000                   | 3.4       | 270                | 80                | >90   | >55     | 3.74                      | 833.75.178 |




Recess mount housing







Surface mount housing







- > Lead, 1.5 A/24 AWG, with snap-in connector for multi-white lights
- > Length: 2000 mm (78 3/4")

| Voltage       | Item No.   |
|---------------|------------|
| 5 12V         | 833.95.787 |
| <b>5</b> 24 V | 833.95.790 |



> Housing, recess mounted, Plastic

| Color                   | Round      | Square     |
|-------------------------|------------|------------|
| Black                   | 833.72.168 | 833.72.172 |
| Anthracite              | 833.72.380 | 833.72.383 |
| Brown                   | 833.72.381 | 833.72.384 |
| Matt nickel-plated      | 833.72.170 | 833.72.174 |
| Stainless steel colored | 833.72.382 | 833.72.385 |
| Silver colored          | 833.72.126 | 833.72.127 |
| White, RAL 9003         | 833.72.171 | 833.72.175 |
|                         |            |            |



> Housing, surface mounted, Plastic

| Color                   | Round      | Square     |
|-------------------------|------------|------------|
| Black                   | 833.72.160 | 833.72.164 |
| Anthracite              | 833.72.193 | 833.72.195 |
| Brown                   | 833.72.192 | 833.72.196 |
| Matt nickel-plated      | 833.72.162 | 833.72.166 |
| Stainless steel colored | 833.72.194 | 833.72.197 |
| Silver colored          | 833.72.124 | 833.72.125 |
| White, RAL 9003         | 833.72.163 | 833.72.167 |

Housings are suitable for monochrome and multi-white lights.

\* valid for multi-white plugs.