

PROFESSIONAL POWER WASHERS

DIRECT DRIVE

Tackle every tough cleaning job at work or on the farm. Generac's rugged power washers combine professional-grade features and user-friendly design. They're a breeze to set up, easy to maneuver and won't let you down.



QUICK-CHANGE NOZZLE TIPS Five included, for tackling any job

DURABLE WELDED ROLL-CAGE STYLE FRAME

Protects the engine and pump

STEEL-REINFORCED HOSE

Quick-change connectors make hose connections a snap

PROFESSIONAL-GRADE **ERGONOMIC SPRAY GUN**

Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

PRESSURE CONTROL VALVE

Provides complete control of water pressure for all applications

POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE

Features low-oil shutdown

PROFESSIONAL-GRADE TRIPLEX PUMP

Ceramic-coated pistons mean long life

BELT DRIVE

Powerful. Compact. Long-lasting. These professional-grade power washers feature heavy-duty belt drives for longer pump life than direct drive models. You can also count on a compact, lightweight design for easy mobility around the jobsite.



PROFESSIONAL-GRADE ERGONOMIC SPRAY GUN

Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

HEAVY DUTY BELT DRIVE AR TRIPLEX PUMP

Up to 3X longer life than direct drive triplex pumps

OVERSIZED PNEUMATIC WHEELS

Easily handle rugged jobsite terrain

COMPACT, LIGHTWEIGHT DESIGN

Up to 50 lbs. less weight than other belt-drive power washers

POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE

Features low-oil shutdown









3100-4200 PSI

PROFESSIONAL POWER WASHERS





SPECIFICATIONS

DIRECT DRIVE	3100 PSI	3600 PSI	3800 PSI	4200 PSI
Model Number (49-State/CARB)	6590 / 6607	6855	6564	6565
GPM	2.8	2.6	3.6	4
Cleaning Power (PSI x GPM)	8680	9360	13680	16800
Engine	212cc Generac OHV w/ low oil shutdown	212cc Generac OHV w/ low oil shutdown	302cc Generac OHV w/ low oil shutdown	420cc Generac OHV w/ low oil shutdown
Pump	Triplex with ceramic- coated pistons & pressure adjustment valve			
Spray Gun Type	Professional-grade w/ adjustable side handle			
Hose Type	5/16" x 35' steel reinforced	5/16" x 50' steel reinforced	3/8" x 35' steel reinforced	3/8" x 50' steel reinforced
Soap Tanks	Siphon hose	Siphon hose	Siphon hose	Siphon hose
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap			
Wheel Type	10" never-flat	10" never-flat	10" never-flat	12" pneumatic
Dimensions (L" x W" x H")	31.8 x 24.3 x 38	31.8 x 24.3 x 38	34.5 x 26.8 x 42.5	34.5 x 28.3 x 42.5
Product Weight	102.5 lbs	102.5 lbs	129 lbs	146.5 lbs
Warranty	3 year limited	3 year limited	3 year limited	3 year limited

BELT DRIVE	3800 PSI		
Model Number (49-State/CARB)	6712		
GPM	3.2		
Cleaning Power (PSI x GPM)	12160		
Engine	302cc Generac OHV w/ low-oil shutdown		
Pump Type	Triplex with ceramic-coated pistons & pressure adjustment valve		
Spray Gun Type	Professional-grade w/ adjustable side handle		
Hose Type	5/16" x 50' steel reinforced		
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap		
Wheel Type	10" pneumatic		
Dimensions (L" x W" x H")	35.5 x 25.25 x 26.75		
Product Weight	134 lbs		
Warranty	3 year limited		

 ${\it All portable specifications and models subject to change. Please consult factory for availability.}$

