


Surface mounted light bars

With linkable cable, 24 V

Profile 2103 with Loox LED 3045



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 131A–131B



Note

Designed for use within closet storage spaces.

Components

- > Profile: 2103 - see page 34.
- > LED strip: 3045 - see page 13.
- > Mounting brackets: see page 35.
- > Lead cable: 100 mm (4") male and female

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	3000							
Item No.	833.70.885	833.70.886	833.70.887	833.70.888	833.70.889	833.70.890	833.70.891	833.70.892
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.70.893	833.70.894	833.70.895	833.70.896	833.70.897	833.70.898	–	–
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	–	–
Wattage	7.3	7.6	8.8	9.0	10.2	10.5	–	–
LEDs	84	93	102	111	120	129	–	–
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	4000							
Item No.	833.70.899	833.70.900	833.70.901	833.70.902	833.70.903	833.70.904	833.70.905	833.70.906
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.70.907	833.70.908	833.70.909	833.70.910	833.70.911	833.70.912	–	–
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	–	–
Wattage	7.3	7.6	8.8	9.0	10.2	10.5	–	–
LEDs	84	93	102	111	120	129	–	–
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							