

Trusted Quality. Premium Performance.

For 3 Generations, our team has worked diligently to build strong products with maximum quality, reliability & endurance.

Everflow's New Valve & Hydronics Catalog provides you access to our comprehensive range of valves and related products for commercial and residential applications.

We pride ourselves in providing the finest quality PVF products combined with integrity and dedication to superior customer support. Our national network of distribution centers, allows for increased inventory, shorter shipping times, while providing our customers with the most efficient and cost effective solutions.

Our products meet and exceed national standards, and are approved by many applicable approval agencies.

Our Brands



Our Flagship Brand of Quality Valves & Plumbing Products



Specialty Valves & Hydronic Solutions



Gas Appliance Valves & Connectors



Push to Connect Valves & Fittings

BALL VALVES



605 Series Premium Brass Ball Valve

CSA Approved • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Stainless Steel Ball 1-1/4" - 2", Chrome Plated Ball 1/2" - 1"
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Stem
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- CSA Certified Threaded 1/4" - 2"
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- 600 psi WOG 150 psi WSP
- Temperature Range: -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
605T012-NL	605C012-NL	1/2"	Full Port Ball Valve	10	100
605T034-NL	605C034-NL	3/4"	Full Port Ball Valve	10	100
605T001-NL	605C001-NL	1"	Full Port Ball Valve	5	50
605T114-NL	605C114-NL	1-1/4"	Full Port Ball Valve	5	25
605T112-NL	605C112-NL	1-1/2"	Full Port Ball Valve	5	25
605T002-NL	605C002-NL	2"	Full Port Ball Valve	2	12
605T212-NL	605C212-NL	2-1/2"	Full Port Ball Valve	2	8
605T003-NL	605C003-NL	3"	Full Port Ball Valve	2	6
605T004-NL	605C004-NL	4"	Full Port Ball Valve	2	4

610 Series Premium Brass Ball Valve

UL Listed • CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Stainless Steel Ball
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Stem Design
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- UL Listed 842,125 125 psig
- Certified to FM1140 600 psig 1/4" - 2" IPS, 1/2" - 2" SWT
- CSA Certified 1/2 psig / 5 psig / 125 psig 1/4" - 4"
- 600 psi WOG 150 psi WSP
- Temperature Range: -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
610T014-NL	-	1/4"	Full Port Ball Valve	12	144
610T038-NL	-	3/8"	Full Port Ball Valve	12	144
610T012-NL	610C012-NL	1/2"	Full Port Ball Valve	10	100
610T034-NL	610C034-NL	3/4"	Full Port Ball Valve	10	100
610T001-NL	610C001-NL	1"	Full Port Ball Valve	5	50
610T114-NL	610C114-NL	1-1/4"	Full Port Ball Valve	12	24
610T112-NL	610C112-NL	1-1/2"	Full Port Ball Valve	5	25
610T002-NL	610C002-NL	2"	Full Port Ball Valve	2	12
610T212-NL	610C212-NL	2-1/2"	Full Port Ball Valve	3	6
610T003-NL	610C003-NL	3"	Full Port Ball Valve	2	6
610T004-NL	610C004-NL	4"	Full Port Ball Valve	2	4

BALL VALVES

800 Series High-Grade Ball Valve

RAVEN
SPECIALTY PRODUCTS

Stainless Steel Handle • CSA Certified • Lead Free • Full Port • 600 WOG


- Dezincification Resistant (DZR) Lead Free Brass Material
- Stainless Steel Ball
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Bottom Loaded Stem
- Vinyl Grip Lever Handle
- Stainless Steel Handle
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- UL Listed Threaded
- CSA Certified Threaded
- 600 psi WOG 150 psi WSP
- Temperature Max: 400°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
800T014-NL	800C014-NL	1/4"	Full Port Ball Valve	12	144
800T038-NL	800C038-NL	3/8"	Full Port Ball Valve	12	144
800T012-NL	800C012-NL	1/2"	Full Port Ball Valve	10	100
800T034-NL	800C034-NL	3/4"	Full Port Ball Valve	10	100
800T001-NL	800C001-NL	1"	Full Port Ball Valve	5	50
800T114-NL	800C114-NL	1-1/4"	Full Port Ball Valve	12	24
800T112-NL	800C112-NL	1-1/2"	Full Port Ball Valve	5	25
800T002-NL	800C002-NL	2"	Full Port Ball Valve	2	12
800T212-NL	800C212-NL	2-1/2"	Full Port Ball Valve	3	6
800T003-NL	800C003-NL	3"	Full Port Ball Valve	2	6
800T004-NL	800C004-NL	4"	Full Port Ball Valve	2	4

615 Series Lead Free T-Handle Brass Ball Valve


CSA Approved • Lead Free • T-Handle with Vinyl Grip • Full Port • 600 WOG


- Dezincification Resistant (DZR) Lead Free Brass Material
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut & Packing On The Stem Seal
- Stainless Steel Ball
- Vinyl Grip T-Handle
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- CSA Certified to: NSF/ANSI-61, NSF/ANSI-372, IGC-157
- 600 psi WOG 150 psi WSP
- Temperature Range: -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
615T014-NL	-	1/4"	Full Port Ball Valve	10	100
615T012-NL	615C012-NL	1/2"	Full Port Ball Valve	10	100
615T034-NL	615C034-NL	3/4"	Full Port Ball Valve	10	100
615T001-NL	615C001-NL	1"	Full Port Ball Valve	5	50

BALL VALVES

L-610 Series Premium Lock Handle Ball Valve

RAVEN
SPECIALTY PRODUCTS

UL Listed • CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Latch Lock Handle with Vinyl Grip
- Forged Brass Body
- Stainless Steel Ball
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Stem Design
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- UL Listed 842,125 125 psig
- Certified to FM1140 600 psig 1/4" - 2" IPS, 1/2" - 2" SWT
- CSA Certified 1/2 psig / 5 psig / 125 psig 1/4" - 4"
- 600 psi WOG 150 psi WSP
- Temperature Range: -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
L-610T012-NL	L-610C012-NL	1/2"	Lock Handle Ball Valve	10	100
L-610T034-NL	L-610C034-NL	3/4"	Lock Handle Ball Valve	10	100
L-610T001-NL	L-610C001-NL	1"	Lock Handle Ball Valve	5	50
L-610T114-NL	L-610C114-NL	1-1/4"	Lock Handle Ball Valve	5	25
L-610T112-NL	L-610C112-NL	1-1/2"	Lock Handle Ball Valve	5	25
L-610T002-NL	L-610C002-NL	2"	Lock Handle Ball Valve	2	12
L-610T212-NL	L-610C212-NL	2-1/2"	Lock Handle Ball Valve	2	8
L-610T003-NL	L-610C003-NL	3"	Lock Handle Ball Valve	2	6
L-610T004-NL	L-610C004-NL	4"	Lock Handle Ball Valve	2	4

405 Series Lead Free Brass Ball Valve with Drain



Purge Drain • CSA Approved • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Brass Drain Cap with EPDM Washer
- Forged Brass Body
- Stainless Steel Ball
- PTFE Seats and Seals
- Blow Out Proof Stem
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61/372, IGC-157
- 600 psi WOG 150 psi WSP Service
- Temperature Range: -20°F to 300°F
- CSA Certified
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
405T012-NL	405C012-NL	1/2"	Ball Valve With Drain	10	100
405T034-NL	405C034-NL	3/4"	Ball Valve With Drain	10	100
405T001-NL	405C001-NL	1"	Ball Valve With Drain	5	50

BALL VALVES

855 Series High-Grade T-Handle Ball Valve

RAVEN
SPECIALTY PRODUCTS

Stainless Steel T-Handle • CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Stainless Steel Ball
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Bottom Loaded Stem
- Vinyl Grip T-Handle
- Stainless Steel Handle
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- UL Listed
- CSA Certified
- ISO:9001 Approved Manufacturer

THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
855T012-NL	855C012-NL	1/2"	Full Port Ball Valve	10	100
855T034-NL	855C034-NL	3/4"	Full Port Ball Valve	10	100

825 Series Ball Valve with Drain

RAVEN
SPECIALTY PRODUCTS

Purge Drain • CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Brass Drain Cap with EPDM Washer
- Forged Brass Body
- Stainless Steel Ball
- PTFE Seats and Seals
- Blow Out Proof Stem
- Vinyl Grip Lever Handle
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61/372, IGC-157
- 600 psi WOP 150 psi WSP Service
- Temperature Range: -20°F to 300°F
- CSA Certified
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
825T012-NL	825C012-NL	1/2"	Full Port Ball Valve	10	100
825T034-NL	825C034-NL	3/4"	Full Port Ball Valve	10	100
825T001-NL	-	1"	Full Port Ball Valve	5	50

BALL VALVES

Screwdriver Slotted Ball Valves



620 Series Ball Valve



Lead Free • Screwdriver Slotted Handle • Cast Brass Body •



- Dezincification Resistant (DZR) Lead Free Brass Material
- Screwdriver Slotted Handle
- Cast Brass Body
- Blow Out Proof Stem Design
- Stainless Steel Ball
- Conforms to NSF/ANSI 372
- Pressure Rating is 400 WOG Non Shock
- Temperature Rating is 250°F



PART #	SIZE	DESCRIPTION	INNER	MASTER
620S012-NL	1/2"	Ball Valve W/Screw Driver Slot	10	100
620S034-NL	3/4"	Ball Valve W/Screw Driver Slot	10	120
620S001-NL	1"	Ball Valve W/Screw Driver Slot	6	60

53 Series Long Bonnet Ball Valve



Lead Free • Standard Port • Forged Brass Body • T-Handle With Vinyl Grip



- Long Bonnet T-Handle allows easy shutoff access
- Forged Brass Body
- Chrome Plated Ball
- 175 psi Steam 600 psi WOG
- Temperature Range is -20°C to 120°C
- CSA Approved



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
53122-NL	53121-NL	1/2"	Long Bonnet Ball Valve	10	100
53342-NL	53341-NL	3/4"	Long Bonnet Ball Valve	10	100

Press Long Bonnet Ball Valve

PRESS PART #	SIZE	DESCRIPTION	INNER	MASTER
530R012-NL	1/2"	Press Long Bonnet Ball Valve	10	100
530R034-NL	3/4"	Press Long Bonnet Ball Valve	10	100



BALL VALVES

MIP x FIP Ball Valve


Lead Free • Full Port • 600 WOG

RAVEN
SPECIALTY PRODUCTS



IPS

- Dezincification Resistant (DZR) Lead Free Brass Material
- Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-Ring & PTFE Seal on the Seal
- Stainless Steel Ball
- Vinyl Grip Lever Handle
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- CSA Certified to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- Pressure Rating: 600 psi WOG 150 psi WSP
- Temperature range -20°F to 300°F
- ISO:9001 Approved Manufacturer



PART #	SIZE	DESCRIPTION	INNER	MASTER
600MF012-NL	1/2"	Full Port Ball Valve	10	100
600MF034-NL	3/4"	Full Port Ball Valve	10	100
600MF001-NL	1"	Full Port Ball Valve	5	50

Hose Ball Valve with Cap

Lead Free • Hose Connection • Includes Cap & Chain • Full Port • 600 WOG

RAVEN
SPECIALTY PRODUCTS



IPS

- Dezincification Resistant (DZR) Lead Free Brass Material
- Cap and Seal for Easy Drain and Hose Connection
- Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-Ring & PTFE Seal on the Seal
- Stainless Steel Ball
- Vinyl Grip Lever Handle
- Ends Certified to ANSI B1.20.1 / ASME B16.22
- Press Ends conform to ANSI Z1157
- CSA Approved to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- Pressure Rating: 600 psi WOG 150 psi WSP
- Temperature range -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
THBV-012-NL	CHBV-012-NL	1/2"	Full Port Ball Valve	10	100
THBV-034-NL	CHBV-034-NL	3/4"	Full Port Ball Valve	10	100



SWT



PRESS

PRESS
CONNECT

Press x Hose Ball Valve with Cap

PRESS PART #	SIZE	DESCRIPTION	INNER	MASTER
RHBV-012-NL	1/2"	Press Ball Valve	10	100
RHBV-034-NL	3/4"	Press Ball Valve	10	100

BALL VALVES & ACCESSORIES



300 Series Premium Gas Ball Valve

UL & CSA Certified • Full Port • For Gas and Non Potable Water Use • 600 WOG



300T001-NL



300C001-NL

- Forged Brass Body
- Stainless Steel Ball
- PTFE Stem Packing Seal and Seats
- Blow Out Proof Stem Design
- Ends Conform to ANSI B1.20.1 / ASME B16.22
- Conforms to NSF/ANSI-61, NSF/ANSI-372, IGC-157
- UL Listed 842,125 125 psig
- Certified to FM1140 600 psig 1/4" - 2" IPS, 1/2" - 2" SWT
- CSA Certified 1/2 psig / 5 psig / 125 psig 1/4" - 4"
- 600 psi WOG 150 psi WSP
- Temperature Range : -20°F to 300°F
- ISO:9001 Approved Manufacturer



THREADED PART #	SWEAT PART #	SIZE	DESCRIPTION	INNER	MASTER
300T012	300C012	1/2"	Full Port Ball Valve	10	100
300T034	300C034	3/4"	Full Port Ball Valve	10	100
300T001	300C001	1"	Full Port Ball Valve	5	50
300T114	300C114	1-1/4"	Full Port Ball Valve	5	25
300T112	300C112	1-1/2"	Full Port Ball Valve	5	25
300T002	300C002	2"	Full Port Ball Valve	2	12
300T212	300C212	2-1/2"	Full Port Ball Valve	2	8
300T003	300C003	3"	Full Port Ball Valve	1	6
300T004	300C004	4"	Full Port Ball Valve	1	4

Ball Valve Stem Extension

Solid Brass • Easily Mounts on Ball Valve



- Easy Installation
- Extends Handle Stem for Easy Shutoff Access

PART #	SIZE	DESCRIPTION	INNER	MASTER
STEX1-NL	1/4" 3/8" 1/2"	Ball Valve Stem Extension	1	100
STEX2-NL	3/4" X 1"	Ball Valve Stem Extension	1	100
STEX3-NL	1-1/4" 1-1/2" 2"	Ball Valve Stem Extension	1	100

Stainless Steel Handle w/ Washer & Nut

Stainless Steel with Vinyl Grip Handle



- Stainless Steel Construction
- Vinyl Grip Lever Handle
- Includes Washer and Nut

PART #	SIZE	DESCRIPTION	INNER	MASTER
610HANSS034	3/4"	Stainless Steel Handle	5	50
610HANSS001	1"	Stainless Steel Handle	5	40
610HANSS114	1-1/4"	Stainless Steel Handle	4	20

COMPRESSION BALL VALVES

600M Series Compression Ball Valve



CSA Approved • Lead Free • Compression Connection • Full Port • Vinyl Grip Handle • 600 WOG



600M001-NL

- Dezincification Resistant (DZR) Lead Free Brass Material
- Compression Connection
- Forged Brass Body
- Stainless Steel Ball
- Blow Out Proof Stem
- CSA approved Per NSF/ANSI-61, NSF/ANSI-372, IGC-157
- 600 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20°F to 300°F
- ISO:9001 Approved Manufacturer



PART #	SIZE	DESCRIPTION	INNER	MASTER
600M012-NL	1/2"	1/2" Compression Ball Valve	10	100
600M034-NL	3/4"	3/4" Compression Ball Valve	10	100
600M001-NL	1"	1" Compression Ball Valve	5	50

825M Series Compression Ball Valve with Drain



CSA Approved • Lead Free • Compression Connection • Full Port • Vinyl Grip Handle • 600 WOG



825M034-NL

- Dezincification Resistant (DZR) Lead Free Brass Material
- Compression Connection
- Forged Brass Body
- Stainless Steel Ball
- Blow Out Proof Stem
- CSA approved Per NSF/ANSI-61, NSF/ANSI-372, IGC-157
- 600 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20°F to 300°F



PART #	SIZE	DESCRIPTION	INNER	MASTER
825M012-NL	1/2"	1/2" Compression Ball Valve	10	100
825M034-NL	3/4"	3/4" Compression Ball Valve	10	100
825M001-NL	1"	1" Compression Ball Valve	5	50

Compression Coupling Short

Lead Free • Brass

- Brass Body
- 3" Length - Short Pattern
- Brass Packing Nut



PART #	SIZE	DESCRIPTION	INNER	MASTER
BRCS0012-NL	1/2"	Compression Coupling	10	100
BRCS0034-NL	3/4"	Compression Coupling	12	120
BRCS0100-NL	1"	Compression Coupling	12	96
BRCS0114-NL	1-1/4"	Compression Coupling	12	96
BRCS0112-NL	1-1/2"	Compression Coupling	12	48
BRCS0200-NL	2"	Compression Coupling	1	1

Compression Coupling long

Lead Free • Brass

- Brass Body
- 5" Length - Long Pattern
- Brass Packing Nut



PART #	SIZE	DESCRIPTION	INNER	MASTER
BRCL0012-NL	1/2"	Compression Coupling	24	144
BRCL0034-NL	3/4"	Compression Coupling	12	72
BRCL0100-NL	1"	Compression Coupling	12	48
BRCL0114-NL	1-1/4"	Compression Coupling	12	48
BRCL0112-NL	1-1/2"	Compression Coupling	12	48
BRCL0200-NL	2"	Compression Coupling	12	24

Gas Ball Valves

FLEXTRON®

UL/CSA Approved

Flextron gas ball valves are specially engineered to provide superior performance and reliability. For use with natural, manufactured, mixed liquefied petroleum gases and LP gas-air mixtures.

- Forged Brass Body
- Stainless Steel Ball
- Aluminum Alloy Handle
- Ends conforms to: ANSI B1.20.1
- 600 psi WOG 175 psi WSP
- Temperature Range : -4° F to 149° F
- CSA Approved: ANSI Z21.15/CSA 9.1(1/2psi)
ASME B16.44 / CR91-002 (5psi)
ASME B16.33 / CGA3.16 (175psi)
- UL Listed per: UL 125 (Guide YSDT) 125 WOG



FIP x FIP Gas Ball Valve



PART #	SIZE	DESCRIPTION	INNER	MASTER
FTGV-38F38F	5/8" x 1/2"	FIP x FIP Gas Ball Valve	10	100
FTGV-12F12F	1/2" x 1/2"	FIP x FIP Gas Ball Valve	10	100
FTGV-34F34F	3/4" x 3/4"	FIP x FIP Gas Ball Valve	5	100
FTGV-01F01F	1" x 1"	FIP x FIP Gas Ball Valve	8	60

Flare x FIP Gas Ball Valve



PART #	SIZE	DESCRIPTION	INNER	MASTER
FTGV-58R12F	5/8" x 1/2"	Flare x FIP Gas Ball Valve	10	120
FTGV-58R34F	5/8" x 3/4"	Flare x FIP Gas Ball Valve	10	120
FTGV-12R12F	1/2" x 1/2"	Flare x FIP Gas Ball Valve	10	120
FTGV-38R12F	3/8" x 1/2"	Flare x FIP Gas Ball Valve	5	50

Angle Gas Ball Valve



PART #	SIZE	DESCRIPTION	INNER	MASTER
FTGV-58R34A	5/8" x 3/4"	Flare x FIP Angle Gas Valve	10	120
FTGV-12R12A	1/2" x 1/2"	Flare x FIP Angle Gas Valve	10	120
FTGV-38R12A	3/8" x 1/2"	Flare x FIP Angle Gas Valve	10	120

Flare x Flare Gas Ball Valve



PART #	SIZE	DESCRIPTION	INNER	MASTER
FTGV-38R38R	3/8" x 3/8"	Flare x Flare Gas Ball Valve	10	120
FTGV-12R12R	1/2" x 1/2"	Flare x Flare Gas Ball Valve	10	120

Lever Handle Gas Ball Valve

FLEXTRON®


- Solder Ends
- Forged Brass Body
- Chrome Plated Ball



PART #	SIZE	DESCRIPTION	INNER	MASTER
FTGV-14F14F	1-1/4" x 1-1/4"	FIP x FIP Gas Valve	12	24
FTGV-15F15F	1-1/2" x 1-1/2"	FIP x FIP Gas Valve	9	18
FTGV-02F02F	2" x 2"	FIP x FIP Gas Valve	6	12

GAS BALL VALVES

45 Series FIP Gas Ball Valve



FIP x FIP • Forged Brass Body



- Forged Brass Body
- Stainless Steel Ball
- Blow Out Proof Brass Stem
- Aluminum Alloy Handle
- Thread Ends Conform to: ANSI B1.20.1
- 600 psi WOG 175 psi WSP
- Temperature Range : -4°F to 149°F
- CSA Approved Per: ANSI Z21.15 / CSA 9.1(1/2psi)
ASME B16.44 / CR91-002 (5psi)
ASME B16.33 / CGA3.16 (175psi)
- UL Listed per: UL 125 (Guide YSDT) 125 WOG



PART #	SIZE	DESCRIPTION	INNER	MASTER
4512	1/2"	Gas Ball Valve	10	120
4534	3/4"	Gas Ball Valve	10	120
4501T	1"	Gas Ball Valve	5	50

45Y Series FIP Gas Ball Valve



FIP x FIP • Forged Brass Body



- Forged Brass Body
- Stainless Steel Ball
- Blow Out Proof Brass Stem
- Aluminum Alloy Yellow Handle
- Thread Ends Conform to: ANSI B1.20.1
- 600 psi WOG 175 psi WSP
- Temperature Range : -4°F to 149°F
- CSA Approved Per: ANSI Z21.15 / CSA 9.1(1/2psi)
ASME B16.44 / CR91-002 (5psi)
ASME B16.33 / CGA3.16 (175psi)
- UL Listed per: UL 125 (Guide YSDT) 125 WOG



PART #	SIZE	DESCRIPTION	INNER	MASTER
4512Y	1/2"	Gas Ball Valve	10	120
4534Y	3/4"	Gas Ball Valve	10	120
4501T	1"	Gas Ball Valve	5	50

OP45 One Piece Gas Ball Valve



CSA Approved • Female NPT x Female NPT • Brass Body



- Brass Body
- Plated Steel Handle
- PTFE Ball Seats
- Blow Out Proof Brass Stem
- Thread Ends Conform ANSI B1.20.1
- Pressure Rating: 125 psi (GAS) Service
- Temperature Range: -4°F to 149°F
- CSA Approved: ANSI Z21.15/CSA 9.1 for 1/2 psig
ASME B16.44/CR91-002 for 5 psig
ASME B16.33/CGA3.16 for 125 psig



PART #	SIZE	DESCRIPTION	INNER	MASTER
OP4512	1/2"	Gas Ball Valve	10	120
OP4534	3/4"	Gas Ball Valve	10	120
OP4501	1"	Gas Ball Valve	5	50

S45 Gas Ball Valve w/Screwdriver Slot



CSA & UL Approved • Female NPT x Female NPT • Brass Body



- Brass Body
- Plated Steel Handle
- PTFE Ball Seats
- Blow Out Proof Brass Stem
- Thread Ends Conform ANSI B1.20.1
- Pressure Rating: 125 psi (GAS) Service
- Temperature Range: -4°F to 149°F
- UL Approved 1/2" - 3/4" 125 psig
- CSA Approved: ANSI Z21.15/CSA 9.1 for 1/2 psig
ASME B16.44/CR91-002 for 5 psig
ASME B16.33/CGA3.16 for 125 psig



PART #	SIZE	DESCRIPTION	INNER	MASTER
S4512	1/2"	Gas Ball Valve	10	120
S4534	3/4"	Gas Ball Valve	10	120
S4501	1"	Gas Ball Valve	5	50